



LW / IW / GPW Series In-Wall

The LW, IW and GPW series speakers are quality-built, in-wall speakers. Designed and built to provide fine audio at the most competitive pricing on the face of the earth. The IW Series carries the same life-time warranty by which all TruAudio speakers are known.

The Ghost series in-wall is the latest speaker that incorporates our original US patent to give this speaker its super flush, almost frameless appearance. These speakers also include our new ground-breaking Wave Guide technology, to give the tweeter a fuller dispersion pattern. Each speaker comes with two Wave Guide Tweeters, one straight for standard installations, and a second one that has a 22° angle for off-center installations. The Ghost Series in-wall speaker pushes the concept of aesthetics and incredible performance. A specially designed speaker housing hides the entire frame once the grill is installed. With this new design, the speaker blends seamlessly into the room's environment and is a labor saver.



LW-6



IWP-6



GPW-6

LW-6
speaker Type: In-wall, 2 way
Woofers: 6.5" polypropylene
Tweeter: .75" Mylar
Power: 5 - 60 watts
Impedance: 8 ohms
Freq Response: 55 - 20k Hz
Sensitivity: 88 dB
Grill Type: Micromesh, aluminum
Finish Dims: 12" (304mm) H, 8.63" (219mm) W, 3" (76mm) D
Cutout Dims: 11" (279mm) H, 7.5" (191mm) W
Family:  ARCHES

IWP-6
speaker Type: In-wall, 2 way
Woofers: 6.5" Injected polypropylene
Tweeter: 1" silk soft dome, swivel
Power: 5 - 100 watts
Impedance: 8 ohms
Freq Response: 55 - 20k Hz
Sensitivity: 90 dB
Grill Type: Micromesh, aluminum
Finish Dims: 12.13" (308mm) H, 8.75" (222mm) W, 3" (76mm) D
Cutout Dims: 10.88" (276mm) H, 7.38" (187mm) W
Family:  BRYCE

IWP-8
speaker Type: In-wall, 2 way
Woofers: 8" Injected polypropylene
Tweeter: 1" silk soft dome, swivel
Power: 5 - 125 watts
Impedance: 8 ohms
Freq Response: 41 - 20k Hz.
Sensitivity: 90 dB
Grill Type: Micromesh, aluminum
Finish Dims: 14.13" (359mm) H, 10.13" (257mm) W, 3" (76mm) D
Cutout Dims: 12.75" (324mm) H, 8.75" (222mm) W
Family:  BRYCE

speaker Type:
Woofers:
Tweeter:
Power:
Impedance:
Freq Response:
Sensitivity:
EQ Adjustments:
Grill Type:
Finish Dims:
Cutout Dims:
Family:

GPW-6
speaker Type: In-wall, 2 way
Woofers: 6.5" white polypropylene
Tweeter: 1" silk soft dome
Power: 5 - 100 watts
Impedance: 8 ohm
Freq Response: 45 - 20kHz.
Sensitivity: 89dB (2.83 volts @ 1 meter)
EQ Adjustments: Tweeter & woofer 0, -3, -6
Grill Type: Ghost Style, Frameless
Finish Dims: 12.88" (326mm) H, 9.13" (233mm) W, 3.75" (97mm) D
Cutout Dims: 8" (203mm) H, 11.63" (295mm) W
Family:  POWELL

GPW-8
speaker Type: In-wall, 2 way
Woofers: 8" white polypropylene
Tweeter: 1" silk soft dome
Power: 5 - 125 watts
Impedance: 8 ohm
Freq Response: 40 - 20kHz.
Sensitivity: 90dB (2.83 volts @ 1 meter)
EQ Adjustments: Tweeter & woofer 0, -3, -6
Grill Type: Ghost Style, Frameless
Finish Dims: 14.63" (370mm) H, 10.38" (264mm) W, 3.88" (99mm) D
Cutout Dims: 9.25" (234mm) H, 13.38" (340mm) W
Family:  POWELL