



#### **RGT**

#### **Features**

- · Surge current of 18kA
- Max Power 50W(RMS)
- Frequency range from DC to 2.4GHz
- N-type female connectors
- Waterproof IP67 rated

# **Applications**

- WiFi
- GPS

- DC Pass
- VSWR <1.28:1</li>
- · CE & RoHS compliant
- Bi-Directional
- · Land mobile radio

#### Description

RF surge protector (also known as lightning arrester or surge arrestor) RGT from PolyPhaser, utilizing a gas tube (GT or GDT). This RF surge protector component is manufactured in a coaxial in-line design with wide operating frequency range. All PolyPhaser RF surge protector products are available in stock with same day shipping.

### **Electrical Specifications**

Surge Protector Type DC Handling

Gas Discharge Tube DC Pass

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		2.4	GHz
Impedance		50		Ohms
VSWR			1.28:1	
Insertion Loss			0.25	dB
Operating Voltage (DC)			60	Volts
Input Power, CW			50	Watts
50W @ 10MHz				
10W @ 2GHz				
Surge Current			18	kA
IEC 61000-4-5, 8/20µS WA\	/EFORM			
Throughput Energy			3	mJ

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Type N F/F Bulkhead Coaxial RF Surge Protector, DC - 2.4GHz, 50W, IP67, 60 V Max., 3mJ, 18kA, Gas Discharge Tube RGT





#### **RGT**

### **Mechanical Specifications**

Size

 Length
 3.55 in [90.17 mm]

 Width/Diameter
 1.12 in [28.45 mm]

 Height
 1.32 in [33.53 mm]

 Weight
 0.35 lbs [158.76 g]

Configuration

Input Connector N Female Output Connector N Female

### **Environmental Specifications**

**Temperature** 

Operating Range -50 to +85 deg C

Ingress Protection (IP) Rating IP67

Humidity 90% @ 40°C Vibration 1G @ 5Hz to 100Hz

## **Compliance Certifications**

RoHS CE

#### **Plotted and Other Data**

Notes:


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Type N F/F Bulkhead Coaxial RF Surge Protector, DC - 2.4GHz, 50W, IP67, 60 V Max., 3mJ, 18kA, Gas Discharge Tube RGT





#### **RGT**

### **Typical Performance Data**




Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Type N F/F Bulkhead Coaxial RF Surge Protector, DC - 2.4GHz, 50W, IP67, 60 V Max., 3mJ, 18kA, Gas Discharge Tube RGT





#### **RGT**



PolyPhaser protects and increases the reliability of global RF communications networks, including transportation, telecommunications, defense, security and industrial applications, with superior RF surge protection technologies including DC Block, DC Pass and Ultra Low PIM. Backed by responsive service and expert technical support PolyPhaser continually expands its product offering and services to serve engineers' urgent needs for RF components in mission critical communication networks.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Type N F/F Bulkhead Coaxial RF Surge Protector, DC - 2.4GHz, 50W, IP67, 60 V Max., 3mJ, 18kA, Gas Discharge Tube RGT

URL: https://www.polyphaser.com/type-n-surge-protector-2.4ghz-gas-discharge-tube-rgt-p.aspx

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. PolyPhaser reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. PolyPhaser does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and PolyPhaser does not assume any liability arising out of the use of any part or documentation.

### **RGT CAD Drawing**

