



C000100W404A

Cambium cnPilot E400 802.11ac Managed Access Point

Integrated PoE

PoE (802.3af/at)

Ethernet Speed

1Gbps

Wireless Standards

802.11a , 802.11b , 802.11g , 802.11n , 802.11ac

Bands

2.4GHz , 5.0GHz

Stock Level: **Product in stock**

\$275.00 + GST

Description

Designed for wireless service providers of both enterprise and distributed enterprise networks, the cnPilot E400 offers a WLAN that is scalable, secure, and reliable. The enterprise-grade 802.11ac access points support on-premise or cloud management in a solution that rolls out quickly, blends in to the environment and is easy to operate. E400 APs work well with mesh backhaul, Fiber or can be paired with Cambium's ePMP, PMP 450 or PTP 650 products for long distance reliable backhaul.

Features

- 802.11ac concurrent dual band
- 2x2 MIMO
- 16 SSIDs supporting 256 concurrent users
- Cloud managed with no on-site controller required
- On-board captive portal
- Rate limiting per SSID and client
- Fast roaming across access points (AP)
- Auto channel selection for allocation of wireless spectrum
- Zero touch bulk configuration and provisioning
- Inventory tracking and reporting
- Near real time stats monitoring, aggregation and reporting

Specifications

Details

Manufacturer's Code	FCC (C000100W400A), EU (C000100W401A), AUS/NZ (C000100W402A), BR (C000100W403A) and ROW (C000100W404A) models
Output Power	25dBm
Interfaces	1 Gigabit Ethernet (GigE)
Wireless standards	802.11a/b/g/n/ac
PoE In	802.3af injector or Powered Ethernet switch
Operating System	cnMaestro
Antenna gain dBi	5dBi
Max Power consumption	13W (max)
Number of chains	2x2 MIMO
Dimensions	18 cm x 18 cm x 3 cm

Resources

[Manufacturer Website](#)

[Management Tools](#)

[Downloads](#)

[Forums](#)

Details

Power Injector	48VDC POE Injector
Warranty	Standard 12 Month RTB