



RB922UAGS-5HPacT-NM
MikroTik RouterBOARD RB922UAGS-5HPacT-NM 5Ghz
802.11ac 3x3 Access Point

Wireless Technology

802.11a , 802.11n , 802.11ac

Ethernet Speed

1Gbps

Connectors

RP-SMA

Frequency Category

5GHz

Integrated PoE

PoE (non standard)

Stock Level: **Product in stock**

\$271.00 + GST

Description

The MikroTik RouterBOARD RB922UAGS-5HPacT-NM is equipped with a miniPCI-express slot, a SIM slot for 3G/4G device or additional wireless card, a high power 3x3 triple chain 802.11ac wireless and three RP-SMA connectors for external antennas. The NetMETAL is a completely new 802.11ac product in a waterproof metal enclosure. Its rugged design is made to withstand the toughest conditions, but at the same time is easy to use and can be opened and closed with one hand. The solid aluminum enclosure also works as a reliable heat-sink for its high output power radio. The NetMETAL is equipped with powerful 720Mhz CPU, 128MB RAM, one Gigabit Ethernet port, 802.11ac wireless, one SFP cage, USB, RP-SMA connectors for external antennas and RouterOS L4 license.

Specifications

Details

Product code	RB922UAGS-5HPacT-NM
CPU nominal frequency	720 MHz
CPU core count	1
Size of RAM	128MB
10/100/1000 Ethernet ports	1
MiniPCI-e slots	1
Wireless chip model	QCA9880
Number of USB ports	1
USB slot type	USB type A
PoE In	Yes, 8-30V
Voltage Monitor	Yes
PCB temperature monitor	Yes
Dimensions	143x247x48mm (PCB)
Operating System	RouterOS
License level	4
Max Power consumption	23W
SFP ports	1
Number of chains	3
Output Power	32dBm
Operating Frequency	4920-6100 MHz, Operating range limited by Country Regulations

Resources

[Manufacturer Website](#)

[RouterBOARD Website](#)

[Firmware & Downloads](#)

[FAQs](#)

[Wiki](#)

[Forums](#)

[Go Wireless Help Centre Solutions](#)

Details

Power Supply	24VDC 1.2A PSU
Power Injector	RBGPOE
Mounting Hardware	DIN mount, Hose Clamp, miniPCI screws
Warranty	Standard 12 Month RTB