



RbcAPGi-5acD2nD

MikroTik cAP Dual Band 2.4GHz and 5GHz 802.11ac
Wireless Access Point**Frequency Category**

2.4GHz , 5GHz

Wireless Technology

802.11a , 802.11b , 802.11g , 802.11n , 802.11ac

Ethernet Speed

1Gbps

Integrated PoE

PoE (802.3af/at)

Stock Level: **Sorry! Out of stock!****\$122.00 + GST****Description**

MikroTik cAP Dual Band 2.4GHz and 5GHz 802.11ac Wireless Access Point. The MikroTik cAP ac is a very capable and powerful wireless access point that looks beautiful on both walls and ceilings. The concurrent dual band wireless radio supports dual chain 2 GHz and 5 GHz in 802.11ac and legacy standards, and will provide coverage in 360 degrees around it. Even though the radio supports repeater mode, the two Ethernet ports give you the ability to extend your network with cables, even if PoE power is required, since the cAP ac supports 802.3af/at PoE input on the first port, and passive PoE output (up to 57V) on the second port.

Specifications

Details

Product code	RbcAPGi-5acD2nD
CPU nominal frequency	716 MHz
CPU core count	4
Size of RAM	128 MB
10/100/1000 Ethernet ports	2
Wireless standards	2412 - 2484 MHz; 5150 - 5875 MHz
PoE In	PoE-in 802.3af/at, PoE-out (Passive, Ethernet port 2), 17-57 V
Dimensions	Round case: 136 mm x 136 mm, height: 30 mm; Square case: 145 mm x 145 mm x 30 mm
Operating System	RouterOS
License level	4
Antenna gain DBI	2.5dBi
Max Power consumption	13W
Output Power	26dBm

Resources[Manufacturer Website](#)[RouterBOARD Website](#)[Firmware & Downloads](#)[FAQs](#)[Wiki](#)[Forums](#)[Go Wireless Help Centre Solutions](#)

Details

Power Supply 24VDC 1.2A PSU

Power Injector RBGPOE

Mounting Hardware Ceiling Mount